

AirLink Antenna Datasheet



AirLink® Antenna: High Gain Directional

The Internal Wi-Fi/Bluetooth is tested and certified to operate with AirLink routers and gateways. It can be quickly and easily installed on awindscreen or any plastic surface, and is ideal for applications or situations when it is not possible to drill a hole.

With a secure and easy to fit adhesive pad mounting, the Internal Wi-Fi/Bluetooth provides many possibilities for the installer.

		Specification
PART NO.		
		6001127
ELECTRICAL DATA		
Frequency Range		2400-2485MHz
Operational Band		2.4GHz Wi-Fi/Bluetooth
Nominal Polarisation		+/- 45deg
Peak gain	lsotropic	2dBi
Compared to 1/4 wave	••••••	OdBi
Correlation co-efficient	••••••	>0.05%
Pattern	••••••	Omni-Directional
Impedance	••••••	50Ω
Max Input Power	••••••	10W
MECHANICAL DATA		
Dimensions	Height	113mm (4.5″)
	Length	19mm (0.7")
	Depth	2.5mm (0.1")
Operating Temp	••••••	-40° / +80°C (-40° / 176°F)
Material	••••••	TPE
Colour		Black
Weight		52g

		Specification
MOUNTING DATA		
Mounting Type		Adhesive pad
CABLE DATA		
Cable	Cable Type	RG174
	Length	3m (9.8')
	Termination	RP-SMA Plug

About Sierra Wireless

Sierra Wireless is building the Internet of Things with intelligent wireless solutions that empower organizations to innovate in the connected world. We offer the industry's most comprehensive portfolio of 2G, 3G, and 4G embedded modules and gateways, seamlessly integrated with our secure cloud and connectivity services. OEMs and enterprises worldwide trust our innovative solutions to get their connected products and services to market faster.

For more information, visit **www.sierrawireless.com**.

Sierra Wireless, the Sierra Wireless logo, AirLink, and the red wave design are trademarks of Sierra Wireless. Other registered trademarks that appear on this brochure are the property of the respective owners. © 2017 Sierra Wireless, Inc. 2017.05.15

