CONNECT simplifi.







STOP OVERPAYING FOR INTERNET!

- Switch your business to simple LTE wireless internet and save
- Stop losing money when your internet goes out



WORK ANYWHERE

- Connect gives you enterprise-grade internet anywhere it can acquire a solid cellular signal
- Turn your home/rv/boat, construction site, trade show booth into a work site



TRUSTED

- Connect has been selected by major US carriers to be secure and safe to use
- Connect is the best value in the market



Be resilient in work & play:

Far more than a hotspot Simplifi, has all your home and small business connectivity needs covered.



Resiliency



Security

IPsec, UAM/Radius, SPI/Firewall, port forwarding, cellular to ethernet connection



Connected

Complete network in a box, 32 WiFi Connections, connected to fixed wire line and/or LTE, 4G, 3G, 2G



Simplicity

Plug n' play, set and forget Remote management platform for easy configuration



Portability

No moving parts, no external antennas, works anywhere there is cellular connection



Reliable

24 hour support, Enterprise grade solution

Ready to join The Resiliency?

Contact

Sales@Simplifi.io 239-919-8551

Networks	BS6425L-AF-11 LTE FDD: B2/B4/B5/B12/B13/B14/B66/B71 WCDMA: B2/B4/B5 BS6425L-A-11 LTE FDD: B2/B4/B12 WCDMA: B2/B4/B5 BS6425L-V-11 LTE FDD: B4/B13
Data Speeds	LTE - FDD CAT4 Max150Mbps (DL), Max 50Mbps (UL) DC-HSPA+ DL 42 Mbps HSUPA - UL 5.76Mbps
WLAN	Dual-Band/802.11 b/g/n/ac, WPA/WPA2/WPA2 Enterprise
USB (3.0)	USB (Host) HS and FS
LAN (10/100/1000 Base-T)	RJ-45 Modular Jack on side panel for TCP / IP, PPP, UDP
SIM	1.8V and 3.0V standard USIM (2FF)
LED Indicators	Cellular network status (1 ea.) LAN traffic (1 ea.) USB traffic (1 ea.)
Power Supply Requirements	120 /240 VAC at 10VA (10W) max

Outline Dimensions (Less AC prongs and mounting tab)	4.1" (104mm) Height 2.2" (56mm) Width 2.0" (51mm) Depth
Weight	7 oz (198 g)
Operating Temperature	-10°C to +40°C
Storage Temperature	-30°C to +70°C
Approvals	PTCRB, 3GPP FCC parts 2 and 15 CE, TUV