BR1 Mini Core





High Level of Security Compliance

Designed with strict security compliance in mind, we've tailor-made the device to exclude Wi-Fi & GPS functionality, making it great for networks that require a highly secure connection.











Full GPIO functionality

Seamlessly integrate telemetry devices into your network with the BR1 Mini Core's built-in I/O functionality.

Power through AC/DC

Now available for purchase with DC cables, we aim to make it easy for our users to sync up all their devices with zero hassle.

Certified safe for work

With UL and Class 1 Division 2 certifications, among many others, the BR1 Mini Core is ready to handle demanding setups.



BR1 Mini Core





Specifications

WAN Interface	1x 10/100/1000M Ethernet ¹ 1x Embedded Cellular Modem with	Antenna Connectors	2x SMA Cellular Anetenna Connectors
	Redundant SIM Slots	Power Input	Power Port: 10V – 30V DC AC Adapter: AC Input 100V–240V / DC Output 12V
LAN Interface	2x 10/100/1000M Ethernet	Power Consumption	10W (nominal), 16W (max.)
SpeedFusion features	Hot Failover¹ / WAN Smoothing¹	Dimension	5.0 x 4.2 x 1.4 inches / 125.7 x 107 x 35 mm
Number of PepVPN SpeedFusion Peers	2/5 ²	Weight	0.95 pounds / 430 grams
Feature	GPIO	Operating Temperature	-40° – 149°F / -40° – 65°C
Router Throughput	300Mbps	Humidity	15% – 95% (non-condensing)
PepVPN Throughput (No Encryption)	80Mbps	Certifications	FCC, CE, RoHS UL+CUL (62368-1)
PepVPN Throughput (256-bit AES)	20 Mbps / 60Mbps ²	Package Content	UL 121201 (Class I and Division 2) 1x BR1 Mini Core
Recommended Users	1-60	-	2x LTE Antennas (ACW-235) 1x 12V 2A 4pin Power Supply (ACW-632)
Cellular Data Rate³ (Downlink/Uplink)	CAT-4: 150 Mbps/50 Mbps	SIM Card Size	Nano-SIM (4FF)
		Warranty	1-Year Limited Warranty

¹ Available with a feature pack add-on license. ² Requires a PrimeCare subscription, complimentary for the first year. ³ Maximum theoretical data rate.

Specifications are subject to change without notice.

BR1 Mini Core



Ordering Information

Product Code MAX-BR1-MINI-LTE-US-T-M-PRM Embedded Modem(s): 1x CAT-4	Regions North America* *US Carrier Certifications: AT&T, FirstNet, T-Mobile, Verizon	LTE Bands B2, B4, B5, B12, B13, B14, B66, B71	3G Bands WCDMA/HSPA+/DC-HSPA+: B2, B5
MAX-BR1-MINI-LTE-E-T-PRM Embedded Modem(s): 1x CAT-4	APAC, EMEA	B1, B3, B5, B7, B8, B20, B38, B40, B41	WCDMA/HSPA+/DC-HSPA+: B1, B5, B8
MAX-BR1-MINI-LTE-MX-T-PRM Embedded Modem(s): 1x CAT-4	APAC, Latin America, Australia	B1, B2, B3, B4, B5, B7, B8, B28, B40	WCDMA/HSPA+/DC-HSPA+: B1, B2, B5, B8

Featured Add-on

Product Code	Description
PRM-MAX-BR1-MINI-1Y	1-Year PrimeCare for BR1 Mini Core
PRM-MAX-BR1-MINI-2Y	2-Year PrimeCare for BR1 Mini Core
PRM-MAX-BR1-MINI-4Y	4-Year PrimeCare for BR1 Mini Core
MAX-BR1-MINI-LC-FP	Feature pack for BR1 Mini Core enables Ethernet WAN, Hot Failover, WAN Smoothing
ACW-634	10ft DC Power Cable
ACW-DIN-BR1-MINI	DIN Rail Mount