



Semtech Antenna – 3-in-1 Bat

Efficient element design assures high performance and robust communication links, this BAT antenna is purposely designed for high-speed Telematics applications and can be mounted on any non-conductive surface. The isolated dual 2G/3G/4G LTE antenna elements cover 698-6000MHz and GNSS. The antenna comes with a low loss flame retardant cable.

		Specification
PART NO.		6001200
ELECTRICAL DATA		
Frequency Range	3G/4G Elements	698-960/1710-3800MHz / 4900-6000MHz
	GNSS	1562-1612MHz
Peak gain: Isotropic¹	3G/4G Elements	2dBi (698-960MHz), 3dBi (1710-2170MHz), 5dBi (2500-3800MHz)
VSWR²	3G/4G Elements	<2.5:1
Isolation²		> 10dB
Pattern		Omni-directional
Impedance		50Ω
Max Input Power		25W
GPS/GNSS DATA		
Frequency Range		1562-1612MHz
VSWR		<2:1 ± 4MHz
Gain: LNA		26dB
Polarisation		Right Hand Circular
Operating Voltage		3-5V DC
Current		Typical <20mA
Approvals		E11

¹ Peak gain does not include cable attenuation
² VSWR & Isolation measured on 3mm thick ASA with 3m (10') of CS29 cable

MECHANICAL DATA		Specification
Dimensions	Height	16.5mm (0.65")
	Length	214mm (8.4")
	Width	77mm (3.0")
Operating Temp		-30° / +70°C (-30° / 158°F)
Material		ASA
Color		Black
Weight		350g
MOUNTING DATA		
Mounting Type		Adhesive
CABLE DATA		
Cell / LTE Cables	Cable	CS29
	Length	3m (10ft)
	Termination	SMA Plug
GPS Cable	Cable	RG174
	Length	3m (10ft)
	Termination	SMA Plug

About Semtech

Semtech Corporation (Nasdaq: SMTC) is a high-performance semiconductor, IoT systems and cloud connectivity service provider dedicated to delivering high-quality technology solutions that enable a smarter, more connected and sustainable planet. Our global teams are committed to empowering solution architects and application developers to develop breakthrough products for the infrastructure, industrial and consumer markets.

To learn more about Semtech technology, visit us at [Semtech.com](https://www.semtech.com) or follow us on [LinkedIn](#) or [X](#).